



ERP15-20VT



Key features

Primary Task: **Lifting and Stacking**

Environment: **Indoor, Outdoor**

Load Weight: **1500-2000 kg**

Max Lift Height: **3215-5500 mm**

Power Source: **Electric**

3 Wheel Electric Forklift Truck Front Wheel Drive

High performance, and energy efficiency combine in the most ergonomically advanced 3 wheel fork lift truck for medium to heavy duty applications

The VT series electric counterbalanced forklift trucks compact design allows operation in the narrowest of aisles and also provides best-in-class manoeuvrability.

Energy efficiency and productivity can be matched to suit application needs while the unique 'e-Balance' of these can provide businesses with the best of both worlds.

VT electric fork lift trucks have the widest range of platforms and battery options to ensure whatever shift pattern or application a business demands there is a VT specification that can meet it.

Ergonomic features that provide operator comfort and operational efficiency

- Designed around the shortest to the tallest operator to provide operators with the most comfortable and ergonomic working compartment possible to reduce back strain and minimise fatigue throughout their shift
- An Infinitely adjustable steering column with memory-tilt option and low step height provides easy on and off access
- A fully adjustable full suspension low vibration seat (0.3-0.6m/s²) helps reduce the transmission of truck vibration to the operator and provides a smooth ride
- The 'heads up' display keeps your operators field of vision clear and provides 'at a glance' information on truck operating conditions and performance settings
- An adjustable mini-lever module armrest with built-in hydraulic controls, directional switch, emergency disconnect button and warning horn button ensures operators stay in control

Performance features that deliver efficient handling and high levels of productivity


- Four performance modes can be accessed through the 'heads up' display allowing a business precise application or operator setting to be selected. Additional settings can be set by a Yale service technician
- The HiP (High Performance) setting delivers a competitive performance of 16.0km/h (laden) while the eLo (Energy Low) setting delivers low energy consumption
- The e-Balance of performance, manoeuvrability and battery shift life can all be matched to an application needs increasing productivity and throughput, significantly reducing the cost per pallet moved
- The YaleStop™ feature is automatically set by the control system so the park brake is always set whenever the truck is stationary and traction has not been requested this provides operators with confidence when picking and depositing loads or working on gradients

Model	Load Capacity (kg)	Lift Height (mm)	Battery Capacity (V / Ah)	radius	centre
ERP15VT (SWB)	1500	5500	48V / 500Ah	1476	500
ERP16VT (SWB)	1600	5500	48V / 500Ah	1476	500
ERP16VT (MWB)	1600	5500	48V / 625Ah	1575	500
ERP16VT (LWB)	1600	5500	48V / 750Ah	1676	500
ERP18VT (MWB)	1800	5500	48V / 625Ah	1575	500
ERP18VT (LWB)	1800	5500	48V / 750Ah	1676	500
ERP20VT (MWB)	2000	5500	48V / 625Ah	1575	500
ERP20VT (LWB)	2000	5500	48V / 750Ah	1676	500



ERP15-20VT - Specification Sheet

VT, VF and VL Range - Brochure

Yale® czołowe wózki widłowe oraz urządzenia magazynowe - Pełna oferta produktowa



WÓZKI NOWE		SERWIS	CZĘŚCI	WÓZKI UŻYWANE	FINANSOWANIE	OUTSOURCING
Oddział Szczecin ul. Szczawiowa 53d 70-010 Szczecin tel. 91 489 33 93 fax 91 482 82 18 szczecin@yale.emtor.pl	Oddział Słupsk ul. Poznańska 83 76-200 Słupsk tel. 59 841 10 64 fax 59 841 10 64 slupsk@yale.emtor.pl	Oddział Gdańsk ul. Glazurowa 7 Kowale, 80-180 Gdańsk tel. 58 301 89 46 fax 58 301 89 46 gdansk@yale.emtor.pl	Oddział Poznań ul. Pilotów 19 Janikowo, 62-006 Kobylnica tel. 61 653 31 57 fax 61 653 31 58 poznan@yale.emtor.pl	Oddział Warszawa ul. Serwituty 25 02-233 Warszawa tel. 22 343 94 85 fax 22 343 94 86 warszawa@yale.emtor.pl	Oddział Wrocław ul. Rakowa 28 51-421 Wrocław tel. 71 325 28 06 fax 71 325 28 20 wroclaw@yale.emtor.pl	Oddział Kraków ul. Cechowa 51 30-614 Kraków tel. 12 659 57 40 fax 12 659 57 40 krakow@yale.emtor.pl
Emtor Sp. z o.o. ■ ul. Włocławska 147-157 ■ 87-100 Toruń ■ tel. 56 654 89 35 ■ fax 56 654 89 36 ■ biuro@yale.emtor.pl ■ www.yale.emtor.pl ■ NIP: 956-213-74-53 ■ Nr KRS: 0000122446 Sąd Rejonowy w Toruniu VII Wydział Gospodarczy KRS ■ Wartość kapitału zakładowego 3.000.000 zł						


 wyłączny przedstawiciel marki 

People. Products. Productivity.