



GLC20-35VX



Key features

Primary Task: **Lifting and Stacking**

Environment: **Indoor, Outdoor**

Load Weight: **2000-3500 kg**

Max Lift Height: **3205-6000 mm**

Power Source: **LPG**

Compact LPG Forklift Truck

Forklift equipment designed for high lift confined space warehouse applications

The Yale Veracitor VX Compact truck series is a feature rich LPG powered fork lift truck series that has been developed specifically for high lift applications in confined areas. They offer high levels of productivity, ergonomics and dependability that deliver low lifetime ownership and running costs.

The 20-35VX models have been engineered to provide users with a model choice dependent on application requirements. Available in two model configurations the Value model is optimised for performance and the lowest cost of operation while the Productivity model delivers maximum performance in heavy duty cycle applications.

Medium to intensive duty work cycle businesses where the VX series excels are:

- Logistics and distribution
- Large warehousing applications
- Manufacturing

Ergonomic features that provide operator comfort and operational efficiency

- Isolated powertrain and full suspension seat result in best-in-class whole body vibration levels of 0.6m/s²
- Operator compartment with clear unobstructed foot space, easy 3 point entry and low step height for easy on and off access
- Infinitely adjustable steering column and ergonomically positioned operators seat with integrated armrest incorporating mini-levers for hydraulic control and other key functions for the most comfortable operating position
- Auto-deceleration system (ADS) automatically decreasing the speed of the truck when the throttle pedal is released minimising brake usage and operator fatigue
- Dash display transmits continuous feedback to the operator of the trucks status and is positioned for optimum visibility


Performance features that deliver efficient handling and high levels of productivity

- The Techtronix 100 transmission features electronic inching which requires no adjustment, electric shift control, neutral start switch, and an anti-restart protection. A single pedal controls both inching and braking.
- Smooth electronic inching, shift and neutral start with brake interlock
- Continuous stability enhancement system (CSE) provides operating confidence from outstanding lateral stability when travelling over uneven ground surfaces and when cornering
- Controlled roll back on ramps for confident operator control on gradients
- Controlled power reversal for regulated directional change and tyre savings
- Intellix vehicle system manager (VSM) maximises uptime by monitoring and protecting key functions of the truck

Model	Load Capacity (kg)	Lift Height (mm)	centre	engine	transmissionb
GLC20VX	2000	6000	500	PSI 2.4L LPG	Techtronix 100 1-Speed
GLC25VX	2500	6000	500	PSI 2.4L LPG	Techtronix 100 1-Speed
GLC30VX	3000	5965	500	PSI 2.4L LPG	Techtronix 100 1-Speed
GLC35VX	3500	5965	500	PSI 2.4L LPG	Techtronix 100 1-Speed
GLC20VX	2000	6000	500	Kubota 2.5L LPG	Techtronix 100 1-Speed
GLC25VX	2500	6000	500	Kubota 2.5L LPG	Techtronix 100 1-Speed
GLC30VX	3000	5965	500	Kubota 2.5L LPG	Techtronix 100 1-Speed
GLC35VX	3500	5965	500	Kubota 2.5L LPG	Techtronix 100 1-Speed

GLC20-35VX - Specification Sheet

Yale® czołowe wózki widłowe oraz urządzenia magazynowe - Pełna oferta produktowa



Oddział Szczecin

ul. Szczawiowa 53d
70-010 Szczecin
tel. 91 489 33 93
fax 91 482 82 18
szczecin@yale.emtor.pl

Oddział Słupsk

ul. Poznańska 83
76-200 Słupsk
tel. 59 841 10 64
fax 59 841 10 64
slupsk@yale.emtor.pl

Oddział Gdańsk

ul. Glazurowa 7
Kowale, 80-180 Gdańsk
tel. 58 301 89 46
fax 58 301 89 46
gdansk@yale.emtor.pl

Oddział Poznań

ul. Pilotów 19
Janikowo, 62-006 Kobylnica
tel. 61 653 31 57
fax 61 653 31 58
poznan@yale.emtor.pl

Oddział Warszawa

ul. Serwituty 25
02-233 Warszawa
tel. 22 343 94 85
fax 22 343 94 86
warszawa@yale.emtor.pl

Oddział Wrocław

ul. Rakowa 28
51-421 Wrocław
tel. 71 325 28 06
fax 71 325 28 20
wroclaw@yale.emtor.pl

Oddział Kraków

ul. Cechowa 51
30-614 Kraków
tel. 12 659 57 40
fax 12 659 57 40
krakow@yale.emtor.pl

Emtor Sp. z o.o. ■ ul. Włocławska 147-157 ■ 87-100 Toruń ■ tel. 56 654 89 35 ■ fax 56 654 89 36 ■ biuro@yale.emtor.pl ■ www.yale.emtor.pl ■ NIP: 956-213-74-53 ■ Nr KRS: 0000122446
Sąd Rejonowy w Toruniu VII Wydział Gospodarczy KRS ■ Wartość kapitału zakładowego 3.000.000 zł



wyłączny przedstawiciel marki

